


Sun-4/200 Series 10-MIPS Processing Power



Sun-4/200 Series 10-MIPS Processing Power

The Sun-4/200 computers are the first members of Sun's new generation of supercomputing workstations and servers. Their impressive processing power is derived from a new 32-bit RISC (Reduced Instruction Set Computer) microprocessor architecture, the Scalable Processor ARCHitecture (SPARC™).

The Sun-4/200 Series of workstations and servers delivers 10-MIPS performance in affordable deskside or cabinet packaging. They are designed to meet the most demanding requirements of engineers and technical professionals in a variety of applications, including mechanical and electronic design and analysis, artificial intelligence, earth resources, image and signal processing, and computational chemistry.

Standard Sun-4/200 Features

- 16.67-MHz (60 ns), 32-bit SPARC architecture CPU
- CPU contains two high-speed 20K CMOS gate-array VLSI chips based on 1.5 micron technology:
 - the SF9010IU Integer Unit
 - the SF9010FPC Floating-Point Control Unit
- Weitek 1164/1165 floating-point arithmetic units
- 128-Kbyte virtual-address, write-back cache memory
- 8-Mbyte ECC main memory boards based on 256 Kbit DRAMS or 32-Mbyte ECC main memory boards based on 1 Mbit DRAMS
- MMU support of 16 register-resident processes, each with 1-Gbyte virtual address space
- 32-bit VMEbus

SPARC Architecture	
Features	Benefits
Large virtual address architecture	Facilitates coding, support, execution of large programs
Single-cycle execution for most 89 SPARC instructions	Simplifies CPU design; speeds overall system performance
32-bit, word-aligned, fixed-format instructions	Simplifies instruction decoding logic for simple design and fast throughput
Load/store, register-register design with 120-register windowed register file	Reduces references to main memory; ensures fast system throughput
Delayed control transfer	Virtually eliminates "wasted" CPU cycles
Four-staged pipelined implementation	Delivers fast throughput, efficient design
Coprocessor support	Accommodates flexible design implementations

- 12-slot card cage
- Ethernet controller
- Two RS-423 ports
- 19-inch landscape high-resolution monochrome monitor (1600 x 1280 pixels)

Options

- Memory expansion to 128 Mbytes with 32-Mbyte boards
- 19-inch landscape color or grayscale monitors (1152 x 900 pixels)
- Graphics Processor and Graphics Buffer boards
- Second Ethernet controller
- Double-height VME board adapter
- SunIPC™ board for IBM PC/AT™ applications software
- 16-Channel Asynchronous Line Multiplexer (ALM)
- High-speed 280-Mbyte or 575-Mbyte ESMD disks
- 60-Mbyte ¼-inch tape cartridge, 1600-bpi or 6250/1600-bpi ½-inch tape subsystems

Sun-4/200 Implementation

The Sun-4 CPU consists of an Integer Unit (IU) chip, a Floating-Point Controller (FPC) chip, two floating-point arithmetic processors, and a large high-speed cache, all connected by a high-speed bus.

Both the IU and FPC chips are implemented in 20K-gate VLSI gate-array chips and are available on the open market.

The 128 Kbyte virtual-address, write-back data and instruction cache augments the CPU for maximum throughput. This high-speed write-back cache feature delivers practically 100% cache hits. The cache delivers one instruction to the processor for every CPU cycle and is completely transparent to programmers.

Using a parallel addressing path, the CPU accesses the cache, main memory, and Memory Management Unit (MMU) simultaneously. If the data is not resident in the cache, the MMU automatically translates the address to main memory. Sun's sophisticated MMU facilitates rapid switching between multiple processes and assures fast main memory cycle time whenever data moves in or out of the cache.



Cover photo: The crisp, clear displays of the Sun-4/200 Series put ECAD and other applications into sharp perspective.



For demanding applications such as those in earth resources, Sun-4/200 supercomputing workstations and servers incorporate the SPARC architecture to cost effectively deliver 10-MIPS performance.

The Sun-4 SPARC processor performs four-stage pipeline operations to optimize instruction execution: *fetch*, *decode*, *execute*, and *write*. As soon as execution control transfers from one stage to the next, a new instruction is delivered. The majority of instructions are executed in a single cycle while the cache performs single-cycle reads. This rapid execution maximizes pipeline efficiency and yields unsurpassed workstation performance.

To enhance reliability, the main memory for the Sun-4/200 Series uses Error Checking and Correction (ECC) codes. With ECC, the system detects and corrects 1-bit-per-byte errors and detects and reports 2-bit errors. Two sizes of memory boards are available for Sun-4 systems: 8-Mbyte boards based on 256-Kbit DRAMs and 32-Mbyte boards based on 1-Mbit DRAMs. These boards can be mixed for a maximum capacity of 128 Mbytes.

An on-board 256-Kbyte frame buffer drives the high-resolution (2-million pixel) monochrome display at Sun's standard 66-Hz non-interlaced refresh rate.

All Sun-4/200 Series electronics are contained on triple-height, quad-depth Eurocard boards. The 32-bit VMEbus offers sustainable I/O access at 8 Mbytes/sec. Mechanical support of additional double-height VME boards is available with an optional card adapter.

Like all Sun Workstation® systems, the Sun-4/200 Series has an open architecture and uses industry standards. The Sun-4™ architecture employs the industry-leading 32-bit VME bus, which is compatible with a large number of board-level components. For its disk interface, it uses the SCSI and ESMD standards, which are compatible with a wide range of mass-storage devices. For data communication, Sun-4/200 workstations use Ethernet and RS-423 interfaces and protocols that are compatible with international, industry, and de facto standards. At the software level, Sun supplies optimizing C, FORTRAN, and Pascal compilers; the UNIX® operating system; the Network File System (NFS™); the X.11/NeWS (Network-extensible Window System); and other standard software interfaces.





Sun-4/200 Series Versatility

The Sun-4/200 Series can be configured as standalone systems with disk and tape backup, as extremely powerful diskless nodes, or as high-performance servers.

Sun-4/200 Configurations

The Sun-4/200 Series can be configured several ways. As a standalone workstation with disk, operating either independently or as part of a network, the Sun-4/260 gives users the ultimate speed and power for even the most demanding, compute-intensive applications.

Without a disk subsystem, the same Sun-4/260 operates as a powerful system on a network, sharing file and printer resources with other network nodes.

As file servers, Sun-4/260S and Sun-4/280S systems deliver optimal performance file sharing for diskless nodes. A single Sun-4/200 server can bolster a network with up to 2.3 Gbytes of high-speed mass storage.

Up to 50 terminals can be connected to a Sun-4/280S acting as a high-speed terminal server. The Sun-4/200 servers can also function as high-speed communication gateways to offload communication-related tasks from other systems.

High-Performance Display Options

The Sun-4/260HM 19-inch monochrome monitor displays clear, crisp images with two mega-pixel resolution arranged in 1600 columns by 1280 rows. The display enhances the clarity of images and fonts because of its 115-dpi (dots per inch) pixel density.

The Sun-4/260C delivers 8-bit color on an 1152 x 900 resolution, 19-inch monitor, simultaneously showing 256 colors of the over-16-million-color palette.

The Sun-4/260G can display 256 shades of gray on an 1152 x 900 resolution, 19-inch grayscale monitor.

For those applications requiring even higher graphic processing performance, optional graphics processors and buffers are available for state-of-the-art transformations, clipping, scaling, and rendering functions.

Mass-Storage Options

By adding a high-speed 280-Mbyte disk subsystem with a 60-Mbyte, 1/4-inch streaming cartridge backup tape, you can configure a Sun-4/260 as a standalone workstation. A second 280-Mbyte disk puts 560 Mbytes in the companion pedestal.

The Sun-4/260S network server can accommodate up to four 280-Mbyte disks, while the Sun-4/280S can hold up to four 575-Mbyte disks. For disk backup, you can use a 60 Mbyte, 1/4-inch cartridge tape or up to two 6250/1600 bpi 1/2-inch tape drives.

Servers

Sun-4/200 Model	260S	280S
Function	Desktop SunServer™	Data Center SunServer
Card Cage	12-slot	12-slot
Disk Drives	280 Mbytes to 1.1 Gbytes	280 Mbytes to 2.3 Gbytes
Serial Ports	18 max.	50 max.
Tape Backup	60 Mbyte, 1/4-inch	60 Mbyte, 1/4-inch or 6250/1600 bpi, 1/2-inch


Workstations

Sun-4/200 Model	260HM	260C	260G
Function	Desktop monochrome workstation	Desktop color workstation	Desktop grayscale workstation
Display Type	19-inch high-resolution monochrome	19-inch color	19-inch grayscale
Resolution	1600 x 1280	1152 x 900	1152 x 900
Dots per inch	115	81	81
Refresh Rate	66 Hz	66 Hz	66 Hz
Card Cage	12-slot	12-slot	12-slot
Disk Drives	280 Mbytes to 1.1 Gbytes	280 Mbytes to 1.1 Gbytes	280 Mbytes to 1.1 Gbytes
Tape Backup	60 Mbyte, 1/4-inch	60 Mbyte, 1/4-inch	60 Mbyte, 1/4-inch

Mass Storage Subsystems

	Disk Drives		Tape Drives	
	10 1/2-inch	8-inch	1/2-inch	1/4-inch
Capacity	575 Mbytes	280 Mbytes	150 Mbytes	60 Mbytes
Access Time	18 msec	20 msec	N/A*	N/A
Disk Transfer Rate	2.4 Mbyte/sec	2.4 Mbyte/sec	N/A	N/A
Interface	ESMD	ESMD	Pertec	SCSI
Tape Density	N/A	N/A	6250/1600 bpi	10,000 bpi
Tape Speed	N/A	N/A	75 ips Streaming 25 ips Start/Stop	90 ips Streaming Cartridge
Sun-4 System	280S only	all 260s	280S only	all

*N/A = not applicable



For mechanical and civil engineers, the high performance of the Sun-4/200 Series helps tie all the pieces of your design together.

The Sun-4 Environment

The Sun-4 family of computers is based on industry standards, making the Sun-4/200 Series compatible with the other members of the Sun-3™ and Sun-2™ product lines. Even though the Sun-4 family is based on a powerful new architecture, Sun has maintained 100% source-code compatibility with Sun-2 and Sun-3 product families. Most existing software applications require only a recompilation to migrate to and take advantage of the supercomputing performance that the Sun-4/200 Series delivers.

All of Sun's software offerings are available on the Sun-4 systems. In addition, more than 900 software packages are available through the Sun Catalyst Third Party Program.

Sun's Open System Network (OSN™) is the realization of a true heterogeneous, distributed computing environment. OSN includes the Open Network Computing (ONC™) environment, the SunLink™ data communication products, and the merged NeWS™ and X Window System.™ ONC comprises NFS, Yellow Pages, and Remote Execution (REX), for transparent access to file structures over the network, even to other vendors' computers with different operating systems or architectures.

Sun has extensive data communication links over both local and wide areas, and across a variety of vendors' systems. Sun provides a link to IBM mainframe systems through the SunLink SNA 3270, BSC 3270, X.25, BSC RJE, LU6.2, Channel Adapter, and OSI options. The SunLink DNI and TE100 products put your system in touch with DEC* and other systems running DECnet™ VAX protocols.

The Sun PC-NFS™ and SunIPC products provide a link to IBM PCs. PC-NFS brings NFS capability to IBM PCs on

a local area network. SunIPC puts PC-DOS application software in a window on a Sun workstation.

All Sun systems use Sun's implementation of the UNIX operating system, which combines Berkeley 4.2BSD and AT&T System V versions into the powerful Sun Operating System (SunOS). Sun enhanced the UNIX systems for networked workstations and added the SunPro™ software programming environment; the SunView™ window-management and interface development system; the SunCore,* SunCGI™, and SunGKS™ graphics libraries; as well as C, VMS FORTRAN, Pascal, Sun Common Lisp, and Modula-2.

To ease migration of code to and from Sun-2, Sun-3, and Sun-4 systems, a 68010/68020-to-SPARC and SPARC-to-68010/68020 cross-compiler is optionally available. Sun protects your software investment by ensuring compatibility among existing and future Sun systems and by encouraging the integration of new technologies with existing resources.

Sun-4 Applications

The Sun-4/200 Series comprises general-purpose engineering workstations and servers with especially enhanced performance for integer and floating-point arithmetic, graphics, and I/O-intensive applications. The Sun-4/200 Series systems are particularly well suited for ECAD logic simulation, IC and PCB layouts, design and electrical rules check applications, and for MCAD finite element analysis, solids modeling, and thermal and stress analysis applications. The Sun-4/200 Series' unsurpassed power and speed provide the ideal platform for AI software development,

signal and image processing, and general education and research environments.

With expanded mass storage, Sun-4/200 workstations and servers become extremely cost-effective, powerful integrated software development environments. These systems, when networked as file-servers with multiple Sun-3 diskless nodes, can maximize performance for all applications, ultimately reducing the cost-per-seat over the highest-performance distributed network.

Why RISC?

RISC architecture maximizes performance and speed by performing infrequent functions in software, including in hardware only those features that yield a net performance gain. RISC improves performance by providing the building blocks that can synthesize high-level functions without the overhead of general, yet time-consuming instructions. RISC architectures eliminate complicated instructions requiring excessive microcode support, such as elaborate subroutine calls and text-editing functions. However, RISC architectures retain floating-point functions because these compute-intensive procedures are handled more efficiently in hardware than in software.

RISC designs begin with a necessary and sufficient instruction set. Typically a few simple instructions account for most computation, so these instructions must execute very fast; most SPARC instructions execute in a single CPU cycle. Currently, RISC architectures are about

three to seven times faster than traditional CPU architectures.

Because RISC architectures are easy to implement, they are more portable than traditional architectures, permitting the rapid integration of new technologies. Users will benefit as architectural portability speeds improvements in the cost-performance of computing. With mere recompilation, programs that run on VAX* or 68000-based systems will run much faster on RISC machines.

With the SPARC architecture, Sun has optimized RISC technology. By using the most advanced computer architecture, chip, memory and cache technologies, the Sun-4 family cost-effectively achieves unsurpassed processing power. The Sun-4 workstations and servers address application areas that previously required special-purpose computer architectures or large, expensive mainframe- or supercomputer-level systems.

Sun-4/200 Series Specifications

Central Processor Type	SF9010IU, 16.67 MHz	Keyboard Type	94-key, low-profile	Environment Temperature Operating	0° to 40°C (32° to 104°F)
Floating Point Type	SF9010FPC, 16.67 MHz Weitek 1164/1165 IEEE standard 754 32-bit (single), 64-bit (double)	Mouse Type	Optical, 3-button	Nonoperating	-20° to 75°C (-4° to 167°F)
Precision		Software Operating System	Converged UNIX (4.2BSD and AT&T System V) C, FORTRAN, Pascal, Assembler Modula-2, Sun Common Lisp Ethernet, Network File System, TCP/IP SunCore, SunCGI libraries, SunGKS SunView, X.11/NeWS SNA 3270, BSC RJE, BSC 3270, Local 3270, SNA Peer-to-Peer, TE100, DNI, Internetwork Router, X.25, OSI, DDN SunINGRES™ SunUNIFY™ SunSimplify™ SunAlis*	Humidity Operating	20 to 80%, noncondensing @ 40°C
Memory Management Type	Sun-4 MMU	Languages		Nonoperating	95%, noncondensing @ 40°C
Virtual Memory	1 Gbyte per process	Communications		Regulations Meets or exceeds the following requirements:	
Contexts	16 in hardware	Graphics		Safety	UL 478, CSA 154, TUV (VDE 0806, IEC 380)
I/O Interface	DVMA™	User Interfaces		RFI/EMI	FCC Class A, VDE 0871
Main Memory RAM	8 Mbytes or 32 Mbytes ECC standard	SunLink Communication		X-ray Emissions	DHHS Rule 21 (Subchapter J), PTB 15 KV—no hard errors
Expansion RAM	8-Mbyte boards (256 Kbit) 32-Mbyte boards (1 Mbit) 128 Mbytes	Database		Static Discharge	
Maximum RAM Memory to Cache	64 bits	Office Automation		Ergonomics Industrial Design	ZH 1/618 Standards
Bus Width	32 bits	Serial I/O		Electrical	
Cache to Processor	32 bits	I/O Ports	Two RS-423 serial (RS-232C compatible)	AC Voltage	90-132 or 180-264 VAC
Memory Cache Type	Sun-4 Virtual Address Cache	Optional Asynchronous Controller	16-channel for terminals, printers	AC Frequency	47.5 to 66 Hz
Size	128 Kbytes	Optional Multiprotocol Communication Processor (Synchronous)	4-channel for high-speed communications and offloading CPU. Used with SunLink software	Power	1450 VA to system
Organization	Direct map, write-back	Disk Options (up to four drives on two controllers)		Dimensions and Weights 19-inch High-Resolution Monochrome and Grayscale Monitors	
Cycle Time	60 ns	Formatted Capacity	280 Mbytes	Height	44.5 cm (17.5 inches)
Ethernet Interface Media Type	Coaxial cable	Unformatted Capacity	337 Mbytes	Width	46.0 cm (18.1 inches)
Data Rate	10 Mbits/sec	Average Access Time	20 msec	Depth	40.4 cm (15.9 inches)
System Bus Type	VMEbus	Data Rate (ESMD)	2.4 Mbytes/sec	Net weight	24.8 kg (54.5 lbs.)
Address Bus Width	32 bits	Formatted Capacity	575 Mbytes	Shipping weight	27.7 kg (61 lbs.)
Data Bus Width	32 bits	Unformatted Capacity	689 Mbytes	19-inch Color Monitor	
Display Options		Average Access Time	18 msec	Height	44.2 cm (17.4 inches)
High-Resolution Monochrome		Data Rate (ESMD)	2.4 Mbytes/sec	Width	46.7 cm (18.4 inches)
Monitor Format	19-inch landscape	Formatted Capacity	575 Mbytes	Depth	52.3 cm (20.6 inches)
Resolution	1600 (h) x 1280 (v) pixels (115 pixels/inch)	Unformatted Capacity	689 Mbytes	Net weight	34.1 kg (75 lbs.)
Pixel Aspect Ratio	1:1	Average Access Time	18 msec	Shipping weight	37.1 kg (81.5 lbs.)
Refresh Rate	66-Hz non-interlaced	Data Rate (ESMD)	2.4 Mbytes/sec	12-slot Pedestal	
Frame Buffer	256 Kbytes	Tape Options		Height	71.1 cm (28 inches)
Bandwidth	200 MHz	1/4-inch Cartridge Tape		Width	32.5 cm (12.8 inches)
Controls	Brightness, on/off	Drive		Depth	59.7 cm (23.5 inches)
Color and Grayscale		Capacity	60 Mbytes/cartridge	Net weight	84.1 kg (185 lbs.)
Monitor Format	19-inch landscape	Format	QIC-24	Shipping Weight	90.9 kg (200 lbs.)
Resolution	1152 (h) x 900 (v) pixels (81 pixels/inch)	1/2-inch Reel Tape Drive		Keyboard	
Pixel Aspect Ratio	1:1	Capacity	150 Mbytes/reel	Height	4.1 cm (1.6 inches)
Colors Displayed	256	Format	GCR	Width	46 cm (18.1 inches)
Color Palette	16.7 million	Density	6250/1600 bpi	Depth	19.8 cm (7.8 inches)
Refresh Rate	66-Hz non-interlaced			Shipping weight	6.8 kg (15 lbs.)
Frame Buffer	1 Mbyte				
Bandwidth	93 MHz				
Controls	Brightness, degauss, on/off (color) Brightness, contrast, on/off (grayscale)				



The Network Is The Computer™

Corporate Headquarters

Sun Microsystems, Inc.
2550 Garcia Avenue
Mountain View, CA 94043
415 960-1300
TLX 287815

For U.S. Sales Office

locations, call:
800 821-4643
In CA: 800 821-4642

European Headquarters

Sun Microsystems Europe, Inc.
Sun House
31-41 Pembroke Broadway
Camberley
Surrey GU15 3XD
England
0276 62111
TLX 859017

Australia: 61-2-436-4699

Canada: 416 477-6745

France: (1) 46 30 23 24

Germany: (089) 95094-0

Japan: (03) 221-7021

The Netherlands: 02155 24888

UK: 0276 62111

Europe, Middle East, and Africa,

call European Headquarters:

0276 62111

Elsewhere in the world,

call Corporate Headquarters:

415 960-1300

Intercontinental Sales

Specifications are subject to change without notice.

UNIX is a registered trademark of AT&T. PC/AT is a trademark of IBM. X Window System is a trademark of M.I.T. DECnet is a trademark of Digital Equipment Corporation. DEC and VAX are registered trademarks of Digital Equipment Corporation. Sun Microsystems, Sun Workstation, SunCore, and the Sun logo are registered trademarks of Sun Microsystems, Inc. SunIPC, PC-NFS, NFS, DVMA, SunView, SunPro, SunCGI, SunGKS, SunLink, SunSimplify, SunServer, Sun-4, Sun-3, and Sun-2 are trademarks of Sun Microsystems, Inc. SunINGRES is a trademark of Sun Microsystems, Inc., and is derived from INGRES, a product marketed by Relational Technology, Inc. SunUNIFY is a trademark of Sun Microsystems, Inc., and is derived from UNIFY* a registered trademark of Unify Corporation. SunAlis is derived from Alis™ a trademark of Applix, Incorporated. ECAD screen image courtesy of Racal-Redac, Earth Science screen image courtesy of Sierra Geophysics, and CogniSeis Development, Inc. Bio-Medical screen image courtesy of BioDesign, Inc.

Design: Michael Chikamura Design

Photography: Charly Franklin

Printing: Graphic Arts Center

© 1987 Sun Microsystems, Inc.
Printed in USA 7/87 DE 189-0/80K